






 <p>25Amp, 277V</p>		 <p>"ON" Light</p> <p>Red - AC Green - DC</p>									
<p>Plug in Relay Item # 76F-T-2A-[*] List Price \$12.00 [*]Add coil voltage</p>	<p>Socket Item # 76F--06 List Price \$ 5.00</p>	<p>Screw Terminal Relay Item # 76F-BLD-2A-[*] List Price \$17.00</p>	<p>- * Coil Suffix</p> <table border="1"> <tr><td>-G</td><td>24VAC</td></tr> <tr><td>-N</td><td>24VDC</td></tr> <tr><td>-A</td><td>120VAC</td></tr> <tr><td>-C</td><td>240VAC</td></tr> </table>	-G	24VAC	-N	24VDC	-A	120VAC	-C	240VAC
-G	24VAC										
-N	24VDC										
-A	120VAC										
-C	240VAC										

Socket & Relay DIN mount and bolt mount.

Electrical Ratings, 2Pole, N.O.	
25Amp. AC -1 Resistive Current 277 VAC, 25 Amp	Operating Coil Power Consumption Hold In : 2.5VA (AC) 1.9VA (DC)
1.5 HP 120VAC 3.0 HP 240VAC AC-15 Motor Load	Life cycle operations 100,000 Electrical 5,000,000 Mechanical (Above at) 1,800 ops.per hour elect. 18,000 ops. per hour Mech.
Contacts Ag Alloy	-13°F, +133°F Ambient Temp



Dimensions : mm/inches			Relay Version
H	W	D	
50/2"	49/2"	54/2.15"	Screw Terminal
60/2.4"	53/2"	60/2.4"	Relay + Socket



4 Pole Double Throw 10Amp	
	
<p>Plug in Relay Item # JQX-13-KE-4CL[*] List Price \$8.00 [*] Add coil voltage</p>	<p>Socket Item #SKF-14E List Price \$4.50</p>

Electrical Ratings	
10Amp. AC -1 Resistive Current 250 VAC, 10 Amp	Operating Coil Power Consumption Hold In : 1.2VA (AC) 0.9VA (DC)
1/3 HP 120VAC 1/6 HP 240VAC AC-15 Motor Load	Life cycle operations: 1,00,000 Electrical 10,000,000 Mechanical (Above at) 1,800 ops.per hour elect. 18,000 ops. per hour Mech.
Contacts Ag Alloy	-25°F, +158°F Ambient Temp

**4 - FORM "C"
Contacts
(4 - Pole-
Double
Throw)**



Socket mm dimensions		
H	W	D
67	30	30